Anhui Fiate Aviation Co., Ltd. Compact Radial Engines Inc.

MZ202





The MZ202 is a fan air cooled, reed valve controlled 2-cylinder-inline-2-stroke engine with two carburetors and Nikasil coated cylinders. It has one of the highest power to weight ratio available on the 63 HP engine market. The ignition system is fully electronic for maximum reliability and minimum maintenance. The powerful 180 Watt alternator provides ample power for all requirements. The MZ202 weighs a mere 34 kg (including electric starter, carburetors, fuel pump, cooling system, exhaust system). All models are supplied complete with electric starter, wiring harness and exhaust system. Ideally suited for Ultralights, hovercrafts, gyrocopters, light experimental aircrafts and all applications where weight is an issue.

Technical Data (Subject to changes)

Type: Two cylinder two stroke (inline)

 Displacement:
 626 cm³ (38.2cu in)

 Stroke:
 69 mm (2.72 in)

 Bore:
 76 mm (2.99 in)

 Max. performance:
 46.3 kw (63HP) at 6250 rpm

 Max. torque:
 84 Nm (61.9 ft.lb) at 5200 rpm

Carburation: 2 Bing54 carburetors

Ignition System: Dual ignition, CDI programmable

Generator power:180W, 13.8 VCooling:Fan coolingWeight:34 kg (74.96lb)Starting device:Electric starter

Running direction: Counter-clockwise, view to output shaft
Fuel mixture: Mixture 1:50, 2-stroke-oil, fuel min. 95# (RON)

Options

• Gear box RZ2 with clutch (2.55:1, 2.88:1, 3.11:1, 3.66:1)

